

# Electric Trimmers

## Quick & Easy Rotary Trimmers

Wide Format Electric Trimmers are a perfect fit for Sign and Print Shops looking to improve their finishing solutions. Time-Saving features and functions make trimming faster and easier than ever.

### Key Benefits

- **Self-Sharpening Blade** Bi-directional self-sharpening rotary blade easily cuts in both directions
- **Easy to Use** Touch anywhere along the full length activation bar activate the cutting blade or use the included Foot Pedal for hands-free operation
- **Fast Efficient Trimming** Fast 6.6ft/sec blade speeds help reduce trimming time compared to using manual trimmers.
- **Convenient** Sturdy stand with castors makes it easy to move around the workshop.

Available in 65" and 98" trimming widths



**Optional Roll Holder Available**  
 RET-RH1652 – 65" for RET-1652 Trimmer  
 RET-RH2502 – 98" for RET-2502 Trimmer

These economically priced electric trimmers are specifically designed for users to easily and professionally finish wide format graphics. They provide smooth, clean cuts on a wide variety of substrates. Fully featured with fast trimming speeds, a full length activation bar, foot pedal activation, lighted power switch, wastecatcher, built-in safety covers, durable steel floor stand and illuminated guide line all designed for quick and accurate trimming of signs, posters, and various laminated materials.



# Electric Trimmers

## Wide Format Trimmers

### SPECIFICATIONS



TRIMMER MODEL	RET-1652	RET-2502
<b>Max Cutting Size</b>	65"	98"
<b>Max Cutting Thickness</b>	0.8mm	0.8mm
<b>Max Cutting Speed</b>	6.6 ft/sec.	6.6 ft/sec.
<b>Recommended Materials:</b>		
<b>Canvas</b>	20mil (0.50mm)	20mil (0.50mm)
<b>Laminate</b>	15mil (0.38mm)	15mil (0.38mm)
<b>Lexan</b>	10mil (0.25mm)	10mil (0.25mm)
<b>Paper</b>	30mil (0.80mm)	30mil (0.80mm)
<b>Styrene</b>	10mil (0.25mm)	10mil (0.25mm)
<b>Vinyl</b>	20mil (0.50mm)	20mil (0.50mm)
<b>Cutting Method</b>	Rotary Blade	Rotary Blade
<b>Stand Included</b>	Yes	Yes
<b>Castors</b>	Yes	Yes
<b>Open-Back Design</b>	Yes	Yes
<b>Bi-Directional Cutting</b>	Yes	Yes
<b>Cutter Activation Bar</b>	Yes	Yes
<b>Waste Catcher</b>	Yes	Yes
<b>Foot Pedal</b>	Yes	Yes
<b>Safety Protection</b>	Interlocking Plexiglas Panel	Interlocking Plexiglas Panel
<b>Feed Roll Holder</b>	Optional	Optional
<b>Feed Table</b>	Yes	Yes
<b>Backlighting</b>	LED	LED
<b>Roll Holder Option</b>	RET-RH1650	RET-RH2502
<b>Unit Weight</b>	143 lbs.	176 lbs.
<b>Dimensions (WxDxH)</b>	83" x 20" x 40"	127" x 20" x 40"
<b>Carton Weight</b>	181 lbs.	234 lbs.
<b>Carton Dimensions WxDxH)</b>	85" x 22" x 16"	132" x 22" x 16"

#### Material Specifications – Maximum Recommended Thickness

*Canvas: 20 mil (0.50 mm) Laminate: 15 mil (0.38 mm) Lexan: 10 mil (0.25 mm)*

*Paper: 31 mil (0.8 mm) Styrene: 10 mil (0.25 mm) Vinyl: 20 mil (0.50 mm)*

